

Purewash 2W Curve

The Solid Surface Purewash 2W Curve is only 312mm deep. The Purewash 2W Curve has a 20mm radiused front edge making it a very safe product for the toilet environment, particularly where there are younger children. Available in a wide range of Solid Surface colours.



Codes	Length	Users	Weight
1202PW/C	1200mm (47 $\frac{1}{4}$ ")	2	40Kg (88lb 2oz)
1802PW/C	1800mm (70 $\frac{7}{8}$ ")	3	56Kg (123lb 7oz)
2402PW/C	2400mm (94 $\frac{1}{4}$ ")	4	71Kg (156lb 8oz)
3002PW/C	3000mm (118 $\frac{1}{8}$ ")	5	87Kg (191lb 12oz)

Technical Data

Warranty	5 years from date of purchase
Solid surface	Corian

Installation Requirements

Brackets	Modular bracket system included
Tension in top fixing location (Unfactored)	2.96kN
Shear in bottom fixing location (Unfactored)	1.92kN
Fixing height	See drawing
Plumbing	Connection to 1 $\frac{1}{2}$ " waste outlet required. Installer to provide water supply for taps. See separate datasheet for ONVO sensor taps.

Related Products

Sensor tap	180
Push tap	260
Soap dispenser	480

Related Documents

Installation manual	email: sales@onvouk.com
Operation and maintenance manual	email: sales@onvouk.com
Warranty document	email: sales@onvouk.com

